



MALE COUPLING

	Thread Size	D2		L2		A/F	
		mm	inch	mm	inch	mm	inch
06 (1/4)	1/4 BSPP	11.8	0.46	35.5	1.40	19.0	0.75
	1/4 NPTF	11.8	0.46	35.5	1.40	19.0	0.75
	7/16-20 UNF	11.8	0.46	35.5	1.40	19.0	0.75
10 (3/8)	3/8 BSPP	17.3	0.68	36.5	1.44	22.0	0.87
	3/8 NPTF	17.3	0.68	36.5	1.44	22.0	0.87
	9/16-18 UNF	17.3	0.68	36.5	1.44	22.0	0.87
12 (1/2)	1/2 BSPP	20.5	0.81	43.5	1.71	27.0	1.06
	1/2 NPTF	20.5	0.81	43.5	1.71	27.0	1.06
	3/4-16 UNF	20.5	0.81	43.5	1.71	27.0	1.06
	7/8-14 UNF	20.5	0.81	43.5	1.71	27.0	1.06
	3/4 NPTF	20.5	0.81	43.5	1.71	27.0	1.06
19 (3/4)	3/4 BSPP	29.1	1.14	57.0	2.24	35.0	1.38
	3/4 NPTF	29.1	1.14	57.0	2.24	35.0	1.38
	1 1/16-12 UN	29.1	1.14	57.0	2.24	35.0	1.38
25 (1)	1 BSPP	34.3	1.35	59.5	2.34	41.0	1.61
	1 NPTF	34.3	1.35	59.5	2.34	41.0	1.61
	1 5/16-12 UN	34.3	1.35	59.5	2.34	41.0	1.61
32 (1 1/4)	1 1/4 BSPP	45.0	1.77	75.0	2.95	50.0	1.97
	1 1/4 NPTF	45.0	1.77	75.0	2.95	50.0	1.97
40 (1 1/2)	1 1/2 BSPP	55.0	2.16	83.5	3.29	60.0	2.36
	1 1/2 NPTF	55.0	2.16	83.5	3.29	60.0	2.36
50 (2)	2 BSPP	65.1	2.56	105.0	4.13	75.0	2.95
	2 NPTF	65.1	2.56	105.0	4.13	75.0	2.95