



MALE COUPLING

		D2		L2		A/F	
		mm	inch	mm	inch	mm	inch
ISO 8434-3	9/16-18 UNF	12.6	0.50	53.0	2.09	19.0	0.75
	11/16-16 UN	12.6	0.50	57.9	2.28	19/22	.75/.87
	13/16-16 UN	12.6	0.50	39.3	1.55	27.0	1.06
ISO 228	1/4 BSPP	12.6	0.50	42.8	1.69	19.0	0.75
	7/16-20 UNF	12.6	0.50	42.5	1.67	17.5	0.69
ISO 8434-2	9/16-18 UNF	12.6	0.50	43.8	1.72	21.0	0.83
	3/4-16 UNF	12.6	0.50	43.3	1.70	22.0	0.87
	1 1/16-12 UN	12.6	0.50	50.8	2.00	32.0	1.26
ANSI B1.20.1	1/8 NPTF	12.6	0.50	43.0	1.69	19.0	0.75
	1/4 NPTF	12.6	0.50	43.0	1.69	19.0	0.75
ISO 11926	7/16-20 UNF	12.6	0.50	43.0	1.69	19.0	0.75
ISO 228	1/4 BSPP	12.6	0.50	39.9	1.57	19.0	0.75
ISO 6149	M14X1.5	12.6	0.50	35.1	1.38	19.0	0.75
ANSI B1.20.1	1/8 NPTF	12.6	0.50	46.8	1.84	19.0	0.75
	1/4 NPTF	12.6	0.50	35.1	1.38	17.0	0.67
ISO 11926	5/16-24 UNF	12.6	0.50	44.8	1.76	19.0	0.75
	7/16-20 UNF	12.6	0.50	46.4	1.83	19.0	0.75
	1/2-20 UNF	12.6	0.50	46.4	1.83	19.0	0.75
	9/16-18 UNF	12.6	0.50	33.1	1.30	17.5	0.69

For all other configurations or thread types please contact the sales office.