



FEMALE COUPLING

	Thread Size	D1		L1		A/F	
		mm	inch	mm	inch	mm	inch
04 (1/8)	1/8 BSPP	20.4	0.80	40.2	1.58	17.0	0.67
	1/8 NPTF	20.4	0.80	40.2	1.58	17.0	0.67
	7/16-20 UNF	20.4	0.80	40.2	1.58	17.0	0.67
06 (1/4)	1/4 BSPP	28.0	1.10	54.0	2.13	27.0	1.06
	1/4 NPTF	28.0	1.10	54.0	2.13	27.0	1.06
	9/16-18 UNF	28.0	1.10	54.0	2.13	27.0	1.06
10 (3/8)	3/8 BSPP	32.0	1.26	69.0	2.72	30.0	1.18
	3/8 NPTF	32.0	1.26	69.0	2.72	30.0	1.18
	9/16-18 UNF	32.0	1.26	69.0	2.72	30.0	1.18
	1/2 BSPP	32.0	1.26	74.0	2.91	30.0	1.18
	1/2 NPTF	32.0	1.26	74.0	2.91	30.0	1.18
	3/4-16 UNF	32.0	1.26	74.0	2.91	30.0	1.18
12 (1/2)	1/2 BSPP	38.0	1.50	83.8	3.30	36.0	1.42
	1/2 NPTF	38.0	1.50	83.8	3.30	36.0	1.42
	3/4-16 UNF	38.0	1.50	83.8	3.30	36.0	1.42
	7/8-14 UNF	38.0	1.50	83.8	3.30	36.0	1.42
	3/4 BSPP	38.0	1.50	83.8	3.30	36.0	1.42
	3/4 NPTF	38.0	1.50	83.8	3.30	36.0	1.42
	1 1/16-12 UN	38.0	1.50	83.8	3.30	36.0	1.42
16 (5/8)	3/4 BSPP	42.0	1.65	83.8	3.30	41.0	1.61
	3/4 NPTF	42.0	1.65	83.8	3.30	41.0	1.61
	1 1/16-12 UN	42.0	1.65	83.8	3.30	41.0	1.61
19 (3/4)	3/4 BSPP	48.0	1.89	99.0	3.90	46.0	1.81
	3/4 NPTF	48.0	1.89	99.0	3.90	46.0	1.81
	1 1/16-12 UN	48.0	1.89	99.0	3.90	46.0	1.81
	1 BSPP	48.0	1.89	99.0	3.90	46.0	1.81
	1 NPTF	48.0	1.89	99.0	3.90	46.0	1.81
	1 5/16-12 UN	48.0	1.89	99.0	3.90	46.0	1.81
	1 BSPP	55.0	2.17	108.5	4.27	55.0	2.17
25 (1)	1 NPTF	55.0	2.17	108.5	4.27	55.0	2.17
	1 5/16-12 UN	55.0	2.17	108.5	4.27	55.0	2.17
	1 1/4 BSPP	55.0	2.17	111.5	4.39	55.0	2.17
	1 1/4 NPTF	55.0	2.17	111.5	4.39	55.0	2.17
	1 5/8-12 UN	55.0	2.17	111.5	4.39	55.0	2.17
	1 1/2 BSPP	80.0	3.15	132.2	5.20	70.0	2.76
32 (1 1/4)	1 1/2 NPTF	80.0	3.15	132.2	5.20	70.0	2.76
	1 7/8-12 UN	80.0	3.15	132.2	5.20	70.0	2.76
	2 BSPP	102.8	4.05	147.3	5.80	80.0	3.15
40 (1 1/2)	2 NPTF	102.8	4.05	147.3	5.80	80.0	3.15
	2 1/2-12 UN	102.8	4.05	147.3	5.80	80.0	3.15