



MALE COUPLING

	Thread Size	D2		L2		A/F	
		mm	inch	mm	inch	mm	inch
04 (1/8)	1/8 BSPP	11.6	0.46	36.5	1.44	17.0	0.67
	1/8 NPTF	11.6	0.46	36.5	1.44	17.0	0.67
	7/16-20 UNF	11.6	0.46	36.5	1.44	17.0	0.67
06 (1/4)	1/4 BSPP	16.1	0.64	53.5	2.11	22.0	0.87
	1/4 NPTF	16.1	0.64	53.5	2.11	22.0	0.87
	9/16-18 UNF	16.1	0.64	53.5	2.11	22.0	0.87
10 (3/8)	3/8 BSPP	19.7	0.78	60.0	2.36	27.0	1.06
	3/8 NPTF	19.7	0.78	60.0	2.36	27.0	1.06
	9/16-18 UNF	19.7	0.78	60.0	2.36	27.0	1.06
	1/2 BSPP	19.7	0.78	63.0	2.48	27.0	1.06
	1/2 NPTF	19.7	0.78	63.0	2.48	27.0	1.06
	3/4-16 UNF	19.7	0.78	63.0	2.48	27.0	1.06
12 (1/2)	1/2 BSPP	24.5	0.97	71.0	2.80	36.0	1.42
	1/2 NPTF	24.5	0.97	71.0	2.80	36.0	1.42
	3/4-16 UNF	24.5	0.97	71.0	2.80	36.0	1.42
	7/8-14 UNF	24.5	0.97	71.0	2.80	36.0	1.42
	3/4 BSPP	24.5	0.97	71.0	2.80	36.0	1.42
	3/4 NPTF	24.5	0.97	71.0	2.80	36.0	1.42
	1 1/16-12 UN	24.5	0.97	71.0	2.80	36.0	1.42
16 (5/8)	3/4 BSPP	27.0	1.06	73.0	2.87	36.0	1.42
	3/4 NPTF	27.0	1.06	73.0	2.87	36.0	1.42
	1 1/16-12 UN	27.0	1.06	73.0	2.87	36.0	1.42
19 (3/4)	3/4 BSPP	29.9	1.18	84.0	3.31	46.0	1.81
	3/4 NPTF	29.9	1.18	84.0	3.31	46.0	1.81
	1 1/16-12 UN	29.9	1.18	84.0	3.31	46.0	1.81
	1 BSPP	29.9	1.18	84.0	3.31	46.0	1.81
	1 NPTF	29.9	1.18	84.0	3.31	46.0	1.81
	1 5/16-12 UN	29.9	1.18	84.0	3.31	46.0	1.81
25 (1)	1 BSPP	36.0	1.42	97.0	3.82	55.0	2.17
	1 NPTF	36.0	1.42	97.0	3.82	55.0	2.17
	1 5/16-12 UN	36.0	1.42	97.0	3.82	55.0	2.17
	1 1/4 BSPP	36.0	1.42	90.4	3.56	55.0	2.17
	1 1/4 NPTF	36.0	1.42	90.4	3.56	55.0	2.17
	1 5/8-12 UN	36.0	1.42	90.4	3.56	55.0	2.17
32 (1 1/4)	1 1/2 BSPP	57.0	2.24	119.7	4.71	70.0	2.76
	1 1/2 NPTF	57.0	2.24	119.7	4.71	70.0	2.76
	1 7/8-12 UN	57.0	2.24	119.7	4.71	70.0	2.76
40 (1 1/2)	2 BSPP	72.9	2.87	173.2	6.82	80.0	3.15
	2 NPTF	72.9	2.87	173.2	6.82	80.0	3.15
	2 1/2-12 UN	72.9	2.87	173.2	6.82	80.0	3.15