



MALE COUPLING

	Thread Size	D1		L2		A/F3	
		mm	inch	mm	inch	mm	inch
06 (1/4)	1/4 BSPP	14.2	0.56	33.0	1.30	19.0	0.75
	1/4 NPTF	14.2	0.56	33.0	1.30	19.0	0.75
	9/16-18 UNF	14.2	0.56	33.0	1.30	19.0	0.75
10 (3/8)	3/8 BSPP	19.0	0.75	40.5	1.59	24.0	0.94
	3/8 NPTF	19.0	0.75	40.5	1.59	24.0	0.94
	9/16-18 UNF	19.0	0.75	40.5	1.59	24.0	0.94
12 (1/2)	1/2 BSPP	20.5	0.81	49.0	1.93	27.0	1.06
	1/2 NPTF	20.5	0.81	49.0	1.93	27.0	1.06
	3/4-16 UNF	20.5	0.81	49.0	1.93	27.0	1.06
19 (3/4)	3/4 BSPP	28.0	1.10	62.0	2.44	34.0	1.34
	3/4 NPTF	28.0	1.10	62.0	2.44	34.0	1.34
	1 1/16-12 UN	28.0	1.10	62.0	2.44	34.0	1.34
25 (1)	1 BSPP	31.3	1.23	73.0	2.87	41.0	1.61
	1 NPTF	31.3	1.23	73.0	2.87	41.0	1.61
	1 5/16-12 UN	31.3	1.23	73.0	2.87	41.0	1.61

For all other configurations or thread types please contact the sales office.