

INDEX: Sewer nozzles

CATEGORY: Nozzles

PERMISSIBLE PRESSURE
RATED TEMPERATURE

300 bar


30 MPa

4350 psi

160 °C

320 °F

CONNECTION	REAR NOZZLES Nr	FRONT NOZZLES Nr	NOZZLE SIZE FP	DIMENSIONS Ø x L mm	WORKING DIAM. mm	WEIGHT g oz	 pz / pcs	NOZZLES KIT	 pz / pcs
G 1/2 F	6 - M 6x8	1 - M 6x8	20	42 x 58	50 ÷ 100	300 10.50	1		1
G 1/2 F	6 - M 6x8	1 - M 6x8	30	42 x 58	50 ÷ 100	300 10.50	1		1
G 3/4 F	6 - M 6x8	1 - M 6x8	30	48 x 60	60 ÷ 150	360 12.70	1		1
G 3/4 F	6 - M 6x8	1 - M 6x8	40	48 x 60	60 ÷ 150	360 12.70	1		1
G 3/4 F	6 - M 6x8	1 - M 6x8	50	48 x 60	60 ÷ 150	360 12.70	1		1
G 3/4 F	6 - M 6x8	1 - M 6x8	60	48 x 60	60 ÷ 150	360 12.70	1		1
G 1 F	6 - M 6x8	1 - M 6x8	50	60 x 78	100 ÷ 300	800 28.20	1		1
G 1 F	6 - M 6x8	1 - M 6x8	60	60 x 78	100 ÷ 300	800 28.20	1		1
G 1 F	6 - M 6x8	1 - M 6x8	80	60 x 78	100 ÷ 300	800 28.20	1		1
NOZZLES CAP KIT									1



MATERIAL: STEEL NICKEL-PLATED

FOR NOZZLE SELECTION SEE CHART A - SECT.28