


Female ORFS Swivel

ISO 12151-1 / ISO 8434-3 / SAE J516



hose	hose Ø	thread	C cut off	HEX
dash	inch	inch	mm	mm
-4	1/4"	9/16" - 18	20.0	17
-4	1/4"	11/16" - 16	23.2	22
-5	5/16"	11/16" - 16	23.5	22
-6	3/8"	11/16" - 16	24.5	22
-6	3/8"	13/16" - 16	25.0	24
-8	1/2"	13/16" - 16	26.5	24
-8	1/2"	1" - 14	29.5	30
-8	1/2"	1.3/16" - 14	30.5	36
-10	5/8"	13/16" - 16	29.0	24
-10	5/8"	1" - 14	30.9	30
-10	5/8"	1.3/16" - 14	30.6	36
-12	3/4"	1" - 14	33.2	30
-12	3/4"	1.3/16" - 14	31.7	36
-12	3/4"	1.7/16" - 12	34.7	41
-16	1"	1.7/16" - 12	34.1	41
-16	1"	1.11/16" - 12	34.0	50
-20	1.1/4"	1.11/16" - 12	36.5	50
-20	1.1/4"	2" - 12	36.5	50
-24	1.1/2"	2" - 12	36.0	60

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating /
ROHS compliant

VERSIONS: Stainless Steel (add an 'S'
at the end of the REFERENCE)