



PARSEC

Furtun TPE pentru aspiratie si ventilatie

Furtun de termoplastic extrem de flexibil pentru transportul aer, gaze, vapori, vapori de vopsea etc. Special construit sa reziste la aer umed si fierbinte la temperaturi de până la 130°C.

Exterior: TPE
 Interior: TPE
 Insertii: Poliester
 Numar insertii: 1
 Culoare exterior: Negru
 Culoare interior: Negru
 Spira: Da

Ø Int. mm	Ø Ext. mm	P.N. bar	P.S. bar	Vacum %	Temp. °C	R.C. mm	Lungime m	Greutate g/m
20		0.5	0	25	-40 - +150°C	20	10	80
25		0.5	0	20	-40 - +150°C	25	10	90
32		0.4	0	20	-40 - +150°C	30	10	140
38		0.4	0	15	-40 - +150°C	38	10	150
40		0.4	0	15	-40 - +150°C	40	10	160
50		0.4	0	10	-40 - +150°C	50	10	210
60		0.4	0	8	-40 - +150°C	60	10	250
70		0.3	0	8	-40 - +150°C	70	10	290
75		0.2	0	7	-40 - +150°C	75	10	310
80		0.2	0	6	-40 - +150°C	80	10	330
100		0.2	0	5	-40 - +150°C	100	10	560
110		0.2	0	5	-40 - +150°C	110	10	600
115		0.2	0	4	-40 - +150°C	115	10	630
120		0.2	0	4	-40 - +150°C	120	10	670
125		0.1	0	4	-40 - +150°C	125	10	700
130		0.1	0	4	-40 - +150°C	130	10	720
140		0.1	0	4	-40 - +150°C	140	10	730
150		0.1	0	4	-40 - +150°C	150	10	780
160		0.1	0	3	-40 - +150°C	160	10	800
175		0.1	0	3	-40 - +150°C	175	10	820
180		0.1	0	2	-40 - +150°C	180	10	850
200		0.1	0	2	-40 - +150°C	200	10	1270
250		0.1	0	2	-40 - +150°C	250	10	1600
300		0.1	0	1	-40 - +150°C	300	10	1450
350		0	0	1	-40 - +150°C	350	10	1550
400		0	0	1	-40 - +150°C	400	10	2000