

MULTIPURPOSE



									
inch	SAE Dash	mm	mm	MPa	PSI	MPa	PSI	mm	kg/m
3/16"	-3	4,8	11,0	2,0	300	6,0	1200	50	0,10
1/4"	-4	6,3	12,8	2,0	300	6,0	1200	60	0,16
5/16"	-5	8,0	14,9	2,0	300	6,0	1200	80	0,24
3/8"	-6	9,5	16,7	2,0	300	6,0	1200	100	0,29
1/2"	-8	12,7	21,0	2,0	300	6,0	1200	125	0,40
5/8"	-10	16,0	24,2	2,0	300	6,0	1200	160	0,50
3/4"	-12	19,0	28,0	2,0	300	6,0	1200	190	0,66
1"	-16	25,4	35,0	2,0	300	6,0	1200	254	0,90
1.1/4"	-20	32,0	42,8	2,0	300	6,0	1200	320	1,20
1.1/2"	-24	38,0	49,8	2,0	300	6,0	1200	380	1,42
2"	-32	50,8	62,2	2,0	300	6,0	1200	510	1,89

INNER TUBE: seamless oil, fuel and gasoline resistant synthetic rubber
REINFORCEMENT: 1 high resistance synthetic fiber braid
SAFETY FACTOR: 3:1

OUTER TUBE: black wrapped, weather and abrasion resistant synthetic rubber
APPLICATION: oil, fuel and gasoline

TEMPERATURE RANGE: -40°C (-40°F) +100°C (+212°F); Max. temperature recommended for water base hydraulic fluids: +70°C (+158°F); Max. temperature recommended for air: +50°C (+122°F)

COVER: U.S. MSHA APPROVED
WARNING: this hose is not according to any particular standards,so should not be used in automotive applications