

Max 2,5 MPa

INDEX: Spray guns

CATEGORY:

PERMISS. PRESSURE WITH METAL NOZZLE 25 bar 2,5 MPa 362 psi
PERMISS. PRESSURE WITH PLASTIC NOZZLE 15 bar 1,5 MPa 217 psi
RATED FLOW 30 l/min 8 USGpm
RATED TEMPERATURE 50 °C 125 °F

MATERIAL

PP/ AISI 316/AISI 304 L

INLET	LENGTH		PLUG COLOR	O-RING MATERIAL	PIPE MATERIAL	WEIGHT		 pz / pcs
	mm	in				g	oz	
G 1/2 F	327	12.87	/BLUE	EPDM	AISI 304 L	252	8.89	10
G 1/2 F	627	24.68	/BLUE	EPDM	AISI 304 L	333	11.75	10
G 1/2 F	927	36.49	/BLUE	EPDM	AISI 304 L	414	14.60	10
G 1/2 F	327	12.87	/RED	VITON®	AISI 304 L	252	8.89	10
G 1/2 F	627	24.68	/RED	VITON®	AISI 304 L	333	11.75	10
G 1/2 F	927	36.49	/RED	VITON®	AISI 304 L	414	14.60	10
G 1/2 F	315	12.40	/BLUE	EPDM	PVC	202	7.13	10
G 1/2 F	615	24.21	/BLUE	EPDM	PVC	235	8.29	10
G 1/2 F	915	36.02	/BLUE	EPDM	PVC	267	9.42	10
G 1/2 F	315	12.40	/RED	VITON®	PVC	202	7.13	10
G 1/2 F	615	24.21	/RED	VITON®	PVC	235	8.29	10
G 1/2 F	915	36.02	/RED	VITON®	PVC	267	9.42	10

OUTLET FILTER (50 MESH) INCLUDED

COMPATIBLE WITH ALCOHOL-BASED PRODUCTS (MAX. 75%), HIGHLY ACIDIC SOLUTIONS AND AGGRESSIVE DETERGENTS (E.G. SODIUM HYPOCHLORITE). IDEAL FOR SANITIZING